

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Everbuild Lumberjack 160

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company : Everbuild – A Sika Company
Site 41
Knowsthorpe Way
Cross Green Industrial Estate
Leeds
West Yorkshire LS9 0SW
United Kingdom

Telephone : 0113 240 3456

E-mail address : everbuild.sds@uk.sika.com

1.4 Emergency telephone number

Emergency telephone number : National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--------------------------------------------------------------------------------------|-------------------------------------------|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

| | | | |
|--------------------------------|---|----------------------|-------------------------------------------------------------------------------------------------------------|
| Hazard statements | : | H225 H319 H336 | Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. |
| Supplemental Hazard Statements | : | EUH066 | Repeated exposure may cause skin dryness or cracking. |
| Precautionary statements | : | P101 P102 | If medical advice is needed, have product container or label at hand. Keep out of reach of children. |
| | | Prevention: | |
| | | P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| | | P271 | Use only outdoors or in a well-ventilated area. |
| | | Response: | |
| | | P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |
| | | Disposal: | |
| | | P501 | Dispose of contents/container in accordance with local regulation. |

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|----------------------------------------------------------------------------------------------------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| ethyl acetate | 141-78-6 205-500-4 01-2119475103-46-XXXX | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066 | >= 20 - < 25 |
| ethanol | 64-17-5 200-578-6 01-2119457610-43-XXXX | Flam. Liq. 2; H225 Eye Irrit. 2; H319 specific concentration limit Eye Dam. 2; H319 >= 50 % | >= 2,5 - < 5 |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 236-675-5 01-2119489379-17-XXXX | Carc. 2; H351 | < 1 |
| methanol | 67-56-1 200-659-6 01-2119433307-44-XXXX | Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 % | < 1 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation
Erythema
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects

Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------|--------------------------|-------------|
| ethyl acetate | 141-78-6 | STEL | 400 ppm 1.468 mg/m3 | 2017/164/EU |
| Further information: Indicative | | | | |
| | | TWA | 200 ppm 734 mg/m3 | 2017/164/EU |
| | | TWA | 200 ppm 734 mg/m3 | GB EH40 |
| | | STEL | 400 ppm 1.468 mg/m3 | GB EH40 |
| ethanol | 64-17-5 | TWA | 1.000 ppm 1.920 mg/m3 | GB EH40 |
| Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used. | | | | |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | TWA (inhalable dust) | 10 mg/m3 | GB EH40 |
| | | TWA (Respirable dust) | 4 mg/m3 | GB EH40 |
| methanol | 67-56-1 | TWA | 200 ppm 260 mg/m3 | 2006/15/EC |
| Further information: Indicative, Identifies the possibility of significant uptake through the skin | | | | |
| | | TWA | 200 ppm 266 mg/m3 | GB EH40 |
| Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity. | | | | |
| | | STEL | 250 ppm 333 mg/m3 | GB EH40 |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|----------------|---------|-----------------|--------------------------|----------|
| methanol | Workers | Skin contact | | 40 mg/m3 |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

| | | | |
|----------|--------------------|--------------|-----------|
| Remarks: | Exposure time: 8 h | | |
| | Consumers | Skin contact | 260 mg/m3 |
| Remarks: | Exposure time: 8 h | | |

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
- #### Environmental exposure controls
- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Appearance : paste
Colour : light brown

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

Odour : solvent-like
Boiling point/boiling range : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 11,5 %(V)

Lower explosion limit / Lower flammability limit : 2,1 %(V)

Flash point : ca. 10 °C
Method: closed cup

Auto-ignition temperature : 427 °C

pH : Not applicable

Viscosity

Viscosity, dynamic : 20.000 - 40.000 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : completely miscible

Vapour pressure : 99,9915 hPa

Density : ca. 1,52 g/cm³ (20 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 1.600 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

methanol:

Acute inhalation toxicity : LC50: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

- ADR : UN 1133
IMDG : UN 1133
IATA : UN 1133

14.2 UN proper shipping name

- ADR : ADHESIVES
IMDG : ADHESIVES
IATA : Adhesives

14.3 Transport hazard class(es)

- ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

- ADR
Packing group : III

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-D

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

- International Chemical Weapons Convention (CWC)
Schedules of Toxic Chemicals and Precursors : Not applicable
- REACH - Candidate List of Substances of Very High
Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).
- REACH - List of substances subject to authorisation
(Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that de-
plete the ozone layer : Not applicable
- Regulation (EU) 2019/1021 on persistent organic pollu-
tants (recast) : Not applicable
- Regulation (EC) No 649/2012 of the European Parlia-
ment and the Council concerning the export and import
of dangerous chemicals : Not applicable
- REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-
jor-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

- Volatile organic compounds : Law on the incentive tax for volatile organic compounds
(VOCV)
Volatile organic compounds (VOC) content: 26,09% w/w
- Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 26,09% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data
Sheet, then it is described in this subsection.

- Health, safety and environ- : Environmental Protection Act 1990 & Subsidiary Regulations
mental regulation/legislation Health and Safety at Work Act 1974 & Subsidiary Regulations
specific for the substance or Control of Substances Hazardous to Health Regulations
mixture: (COSHH)
May be subject to the Control of Major Accident Hazards
Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

SECTION 16: Other information

Full text of H-Statements

| | |
|------|-------------------------------------------|
| H225 | : Highly flammable liquid and vapour. |
| H301 | : Toxic if swallowed. |
| H311 | : Toxic in contact with skin. |
| H319 | : Causes serious eye irritation. |
| H331 | : Toxic if inhaled. |
| H336 | : May cause drowsiness or dizziness. |
| H351 | : Suspected of causing cancer if inhaled. |
| H370 | : Causes damage to organs. |

Full text of other abbreviations

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute Tox. | : Acute toxicity |
| Carc. | : Carcinogenicity |
| Eye Irrit. | : Eye irritation |
| Flam. Liq. | : Flammable liquids |
| STOT SE | : Specific target organ toxicity - single exposure |
| 2006/15/EC | : Europe. Indicative occupational exposure limit values |
| 2017/164/EU | : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values |
| GB EH40 | : UK. EH40 WEL - Workplace Exposure Limits |
| 2006/15/EC / TWA | : Limit Value - eight hours |
| 2017/164/EU / STEL | : Short term exposure limit |
| 2017/164/EU / TWA | : Limit Value - eight hours |
| GB EH40 / TWA | : Long-term exposure limit (8-hour TWA reference period) |
| GB EH40 / STEL | : Short-term exposure limit (15-minute reference period) |
| ADR | : European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | : Chemical Abstracts Service |
| DNEL | : Derived no-effect level |
| EC50 | : Half maximal effective concentration |
| GHS | : Globally Harmonized System |
| IATA | : International Air Transport Association |
| IMDG | : International Maritime Code for Dangerous Goods |
| LD50 | : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : Occupational Exposure Limit |
| PBT | : Persistent, bioaccumulative and toxic |
| PNEC | : Predicted no effect concentration |
| REACH | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : Substances of Very High Concern |
| vPvB | : Very persistent and very bioaccumulative |

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



BUILDING TRUST



Everbuild Lumberjack 160

Revision Date: 05.07.2021

Version 2.0

Print Date 05.07.2021

Date of last issue: 10.12.2020

Further information

Classification of the mixture:

| | |
|--------------|------|
| Flam. Liq. 2 | H225 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN